

# **HLVT/HLVJ** Heat Shrink Termination & Joint For plastic–insulated cables up to 1kV

# ■ Shelf life & storage:

HLVT/HLVJ Heat Shrink Joint & Termination has long shelf life when stored in a humidity controlled storage( $-10^{\circ}$ C to  $40^{\circ}$ C and  $< 75^{\circ}$ 8 relative humidity).



#### **■** Features:

- High mechanical strength
- Wide cross section range suitable for all types of connectors
- Compact dimensions
- Increased UV and weathering stability
- Unanimated shelf life and allows immediate reenergizing

## ■ Key technical performances:

Test Sequence	ltem	Requirements acc to EN50393	Remarks EN50393
1	Impulse withstand voltage test	20kV ±10	PASS
2	AC withstand voltage test(in air and ambient temperature)	4kV,1min	PASS
3	Insulation resistance (in air and ambient temperature)	≥50M Ω	PASS

### ■ Selection table:

#### 0.6/1.0(1.2)kV Heat Shrink Termination

Termination	Cable Insulation OD(mm)	Cable Conductorcross-section (mm²)
HLVT-1.2/4×1.5-10	2.95mm-5.6mm	1.5mm²10mm²
HLVT-1.2/4×16-50	6.4mm-10.0mm	16mm²50mm²
HLVT-1.2/4×70-150	11.5mm-16.9mm	70mm²150mm²
HLVT-1.2/4×185-400	18.5mm-26.5mm	185mm²400mm²

## 0.6/1.0(1.2)kV Heat Shrink Joint

Joint	Cable Insulation OD(mm)	Cable Conductorcross-section (mm²)
HLVJ-1.2/4×1.5-10	2.95mm-5.6mm	1.5mm²10mm²
HLVJ-1.2/4×16-50	6.4mm-10.0mm	16mm²50mm²
HLVJ-1.2/4×70-150	11.5mm-16.9mm	70mm²150mm²
HLVJ-1.2/4×185-400	18.5mm-26.5mm	185mm²400mm²

\*NOTE: 1. Cable insulation outer diameter is one of the prerequisite for cable accessories selection.

- 2. 1-core to 5-core products are available for customize.
- 3. Termination and Joint for 1 core cable can apply up to 1000mm² cable conductor cross-section.

HKIT/HKOT Heat Shrink Termination

HKSJ Heat Shrink Joint

HAT/HATA Medium Voltage Tubing

HAS/HMB/HMR Moulded Parts

HLVT/HLVJ Heat Shrink Termination & Joint

HRSL Heat Shrink Cable Repair Sleeve

HCSIT/HCSOT Cold Shrink Termination

HCSSJ Cold Shrink Joint

HPMC/HPMRC Cable Connector

HCSTT Cold Shrink Trifurcation Kit

HCST Cold Shrink Insulated Tubing

HCMB Cold Shrink 3 Cores Cable Breakout

HCRK-S Cast Resin Straight Through Joints

HCRK-B Cast Resin Branch Joints